



- 360° Positioning Display
- Quick, One Step Calibration
- Waterproof, Corrosion Resistant

820

	820
Flow Rate	2 - 20 GPM / 7 - 75 LPM
Max Pressure	120 PSI / 8,2 bar at 70°F
Inlet/Outlet	1" FNPT Ports
Power Source	2 AA Batteries
Housing Materials	Glass-Filled Polypropylene
Internal Construction	Stainless Steel, PPS
Seals	Fluorocarbon
Calibration	20 Stored Settings
Compatible Fluids	Water, Light Oils, Mild Chemical



900CD

	900CD	900CD1.5
Flow Rate	6 - 40 GPM / 23 - 151 LPM	6 - 40 GPM / 23 - 151 LPM
Max Pressure	50 PSI / 3,5 bar	50 PSI / 3,5 bar
Inlet/Outlet	1" / 1" NPT	1½" / 1½" NPT
Power Source	2 AA Batteries	
Housing Materials	Nickel Plated Aluminum / Aluminum	
Internal Construction	Stainless Steel, Steel, Polyester, Acetal	
Seals	Buna Seals	
Calibration	Ounces, Pints, Quarts, Liters, Gallons and User Defined Units	
Certifications	CE, Ex Certification	
Compatible Fluids	Gasoline, Diesel, BioDiesel up to B20, Kerosene, E15, Mineral Spirits, Stoddard Solvents and Heptane	
Also Available	* Available with BSPT inlet/outlet Model Numbers - 900CDBBSPT, 900CDB1.5BSPT	



900CDP

	900CDP	900CDP1.5
Flow Rate	6 - 40 GPM / 23 - 151 LPM	6 - 40 GPM / 23 - 151 LPM
Max Pressure	50 PSI / 3,5 bar	50 PSI / 3,5 bar
Inlet/Outlet	1" / 1" BSPT	1½" / 1½" BSPT
Power Source	AC Power with use of Barrier	
Housing Materials	Nickel Plated Aluminum / Aluminum	
Internal Construction	Stainless Steel, Steel, Polyester, Acetal	
Seals	Buna Seals	
Calibration	Ounces, Pints, Quarts, Liters, Gallons and User Defined Units	
Certifications	CE, Ex Certification	
Compatible Fluids	Gasoline, Diesel, BioDiesel up to B20, Kerosene, E15, Mineral Spirits, Stoddard Solvents and Heptane	
Also Available	* Available with BSPT inlet/outlet Model Numbers - 900CDPBSPT, and 900CDP1.5BSPT	

